

Sopal CPO-P4


PROPERTIES: Completely soluble in toluene and xylene. The solution has a good fluidity at room temperature. The material has very good weather resisting property, thermal aging resistivity, resistance to chemical attack, oil resistivity, ozone resistivity and fire resistance property.

APPLICATIONS: mainly used as adhesive agent of printing ink and plastics paint. The area of their application is shown as below:

1. Used as adhesive agent of composite printing ink. It is available in producing the printing ink of biaxial oriental polypropylene (BOPP) that is used as packing film of candy and BOPP composite packing.
2. Used in coating of BOPP film, adhesive of BOPP film & paper and the inner coating of pressure sensitive film made from BOPP.
3. This material is also can be used in the laminated board of PP film and aluminum foil, seal agent of joint of PP pipe, flexibility agent of PP fiber, adhesive agent of thermal bonding film and skidproof agent of PP packing.

PACKING: Cartons of 20kgs net each.

QUANTITY: 720kgs per pallet; 16pallets per 20ft container



SPECIFICATIONS:

Appearance	White or Pale Yellow Granular
Viscosity (mPa. s)	100~600
PH Value	6.0~8.0
Content of chloride (%)	28.0~32.0
Volatility (%)	0.5PCT max
ASH	0.3PCT max