



Made in Germany

**One week
delivery**
(within the UAE)



Industrial doors and loading technology

- Industrial Sectional Door
- Industrial Rolling Shutter
- Dock Leveller
- Dock Shelter

HÖRMANN

Doors for Home and Industry

Industrial Sectional Door SPM and SPU F42

Optimum for Loading Technology

Color available RAL 9002



Colour

The outside and inside of the door is Stucco-textured in Grey white (RAL 9002). The Stucco texture makes the surface resilient to dirt and small scratches.

Glazings

Section windows made of scratch resistant DURATEC synthetic glazing allow for a permanently clear view and additional light in the building.

The door sections

The door sections are filled with polyurethane rigid foam. This 42-mm-thick insulating core provides for the convincing robustness and thermal insulation.

Finger trap protection

The unique form of the door sections eliminates trap points, both on the outside and inside. That is valid also for the hinges.

Intermediate seal

Prevents Dust sand dirt from outside and keeps airconditioned inside.

Shaft operator WA 400 – Strong and robust

This patented flange version is simple and quick to fit to the spring shaft and requires considerably less sideroom than the direct drive solutions from other manufacturers.

Optimally sealed

The high-quality seals are permanent elastic and weather-proof. At the ground a bottom profile seal protects against dirt and rain.



Steel Rolling Shutter DRU

Innovative technology for heavy-duty applications

Galvanized steel with transparent protective paint



Support bracket

Made of galvanized sheet steel, reduces the required sideroom on the bearing and operator side.



The belt system

In a special fibrous fabric, connects the shutter curtain to the galvanized, octagonal barrel and dispenses with shutter profiles where these are no longer needed.



Steel side guides

The robust construction in galvanized steel is mounted directly to the building structure.

Thermal insulation

A combination of minimizing thermal bridges and use of finepored polyurethane rigid foam infill ensures good thermal insulation.



Acoustic rated

The curtain as well as the sealing techniques used around the entire shutter help to reduce noise from both outside and inside.




Maximum size:
5000 x 4500 mm
(w x h)

Sealing

The rolling shutters have bristle seals down the side guides and an optional lintel seal is available. The flexible lip seal along the bottom edge adjusts to floor irregularities.

Loading Technology

Complete solutions for more efficiency




Dock Leveller HLS

Color available RAL 5002

The electronic hydraulic system moves the platform to the highest position and then automatically extends the hinged lip. The platform is then lowered until the hinged lip is placed on the loading surface. Now the lorry can be quickly and safely loaded and unloaded. Particularly strong hinges and the continuous hinge band guarantee reliable functioning. The open design keeps the hinges free of dirt.

Available size:
2000 x 3000 mm
(w x l)

Lip length: 405 mm
Lip thickness: 12-14 mm
Rated load: 60 kN



Flap Dock Shelter DSL

Color available RAL 9011

Link arm construction

Due to their special frame profiles, link arms are flexible both horizontally and vertically.

Available size:
3500 x 3500 mm (w x h)

Service

Inspection, maintenance and repair –
with manufacturer's expertise



The after sales and service team, which is comprised of highly skilled technicians, electrical and mechanical engineers, is committed to providing you with the best support and expertise that makes our brand a leading name in the market.

Corrective maintenance

Identify, isolate and rectify a fault in order to restore an asset into an operational condition

Preventive maintenance

Servicing and care for the purpose of maintaining equipment and facilities in a satisfactory operating condition by providing regular inspection, detection and correction of incipient failure either before they occur or before they develop into a major defect.



Available
24 hours
a day
365 days
a year

Contact us now for more information:

+971 4 880 76 77

service.dxb@hormann.com

We operate all over U.A.E.





Showroom

Showcase of innovative solutions for residential and industrial projects

The showroom displays the company's latest products and refurbishment solutions and also features an in house training facility to provide an interactive learning arena and demonstrate its products capabilities in an accessible and user friendly way.

The showroom displays:

- **Industrial Sectional Door SPU 40**
- **Sectional Garage Door LPU 40**
- **Domestic Rolling Shutter RollMatic**
- **Entrance and Internal Doors**
- **Wooden Doors**
- **Industrial Rolling Shutter Decotherm S/SB**
- **Flexible High Speed Door V 5030 SEL**
- **Insulated High Speed Door HS 7030 PU**
- **Sectional Doors ALR 40 N with wicket door and trip-free threshold**
- **Dock Leveler, Dock Shelter and many more items ...**

(not included in the 1 week delivery)



Call Toll Free 800-HORMANN (4676266) for further information
(Only within the U.A.E.)

Hörmann Middle East FZE

Phone: +971 4 880 76 77, Fax: +971 4 880 76 99

P.O. Box 262784, Jebel Ali Free Zone, Dubai, U.A.E.

Email: info.dxb@hormann.com • Web: <http://www.hormann.ae>